



**LM-100**  
**Digital Luxmeter**

- Functions**
- Light measurement
- Product information**
- Manual range selection
  - Silicon sensor
  - Integrated measurement memory (data hold, MAX)

Technical Data	
Display:	LCD 3 1/2-digit
Measurement range:	0...200, 2000, 20,000, 200,000 lux 0...20, 200, 2000, 20,000 fc
Resolution	0.1, 1, 10, 100 lux/ 0.01, 0.1, 1, 10 fc
Accuracy:	< 10%
Power supply:	9 V battery, IEC 6F22
Device dimensions:	130 x 63 x 38 mm
Sensor dimensions:	80 x 55 x 29 mm
Weight:	approx. 220 g

Range  
0,1...  
200 000 Lux

Data  
Hold

Scope of supply:	
1 x LM-100	
1 x 9 V battery, IEC 6F22	
1 x carrying case	
1 x user manual	

Ordering Information:	
Description	Order No.
LM-100	3052348



**LM-120**  
**Digital Luxmeter**

- Functions**
- Light measurement
- Product information**
- Automatic and manual range selection
  - Silicon sensor
  - Integrated measurement memory (data hold, MAX/MIN)
  - Auto power-off
  - Zero adjustment button

Technical Data	
Display:	LCD 3 1/2-digit
Measurement range:	0...20, 0...200, 2000, 20,000, 200,000 lux 0...20, 200, 2000, 20,000 fc
Resolution	0.1, 1, 10, 100 lux/ 0.01, 0.1, 1, 10 fc
Accuracy:	< 10%
Power supply:	9 V battery, IEC 6F22
Device dimensions:	130 x 63 x 38 mm
Sensor dimensions:	80 x 55 x 29 mm
Weight:	approx. 220 g

Range  
0,1...  
200 000 Lux

Data  
Hold

Max  
Hold

Scope of supply:	
1 x LM-120	
1 x 9 V battery, IEC 6F22	
1 x carrying case	
1 x user manual	

Ordering Information:	
Description	Order No.
LM-120	3052353